

**IN THE CLAIMS:**

*Kindly rewrite Claims 1-14 as follows:*

1. (Currently Amended) A method for operating a gas turbo group, which gas turbo group includes at least one combustion chamber, wherein the combustion chamber includes at least one catalytic, first burner stage and a second, non-catalytic burner stage following the at least one catalytic burner stage in the flow direction, the method comprising:  
~~—determining a net power output ( $P_{ACT}$ ) of the gas turbo group;~~  
supplying the gas turbo group with a total fuel mass stream ( $\dot{m}_{FUEL}$ ) of the gas turbo group ~~in relation to a control deviation ( $P_{SET} - P_{ACT}$ ) of the net power output;~~  
distributing the total fuel mass stream to at least the catalytic burner stage and the non-catalytic burner stage;  
determining the temperature ( $T_2$ ) at the outlet from the catalytic burner stage; ~~and~~  
regulating, limiting to a set value, limiting to a maximum value, or combinations thereof, the temperature at the outlet from the catalytic burner stage by changing the combustion air mass stream and blocking the fuel supply to the non-catalytic burner stage when the combustion air mass stream is below an achievable maximum;  
~~—determining a net power output ( $P_{ACT}$ ) of the gas turbo group; and~~  
~~—regulating the fuel mass flow ( $m_{SEV}$ ) to the non-catalytic burner stage depending on a control deviation ( $P_{SET} - P_{ACT}$ ) of the net power output.~~
2. (Previously Presented) A method according to Claim 1, wherein changing the combustion air mass stream comprises adjusting an adjustable guide row of a condenser of the gas turbo group.
3. (Previously Presented) A method according to Claim 2, comprising:  
keeping the adjustable condenser guide row closed when the temperature at the outlet from the catalytic burner stage is below a set value.
4. (Previously Presented) A method according to Claim 1, comprising:  
cooling suction air upstream from the condenser in order to increase the combustion air

mass stream.

5. (Previously Presented) A method according to Claim 4, further comprising:  
injecting fluid droplets into the suction air for cooling.
6. (Previously Presented) A method according to Claim 1, further comprising:  
operating a non-catalytic preburner stage upstream from the catalytic burner stage.
7. (Previously Presented) A method according to Claim 6, further comprising:  
determining the temperature ( $T_1$ ) at the inlet into the catalytic stage; and  
regulating compliance with a minimum value of the temperature at the inlet into the  
catalytic stage by adjusting the fuel mass stream  $\dot{m}_p$  to the preburner stage.
8. (Previously Presented) A method according to Claim 6, comprising:  
operating the preburner stage in a diffusion combustion mode.
9. (Previously Presented) A method according to Claim 1, further comprising:  
in the presence of a maximum combustion air mass stream, supplying a fuel mass stream  
( $\dot{m}_{SEV}$ ) additionally necessary for regulating the net power output to a combustion chamber or  
burner stage located downstream from the catalytic burner stage.
10. (Previously Presented) A method according to Claim 1, further comprising:  
operating the second non-catalytic burner stage as a self-igniting combustion chamber.
11. (Previously Presented) A method according to Claim 1, wherein the regulating  
value of the temperature at the outlet from the catalytic stage corresponds essentially to the  
maximum permissible temperature of the catalyst material.

12. (Previously Presented) A method according to Claim 1, wherein the regulating value of the temperature at the outlet from the catalytic stage is higher than the temperature necessary for a spontaneous self-ignition of the fuel in the second non-catalytic burner stage.
13. (Previously Presented) A method according to Claim 9, wherein the presence of a maximum combustion air mass stream comprises a fully opened adjustable guide row.
14. (Previously Presented) A method according to Claim 9, wherein a combustion chamber or burner stage comprises the non-catalytic burner stage.